

Difusores / Pop-Up sprays

Toberas / Nozzles

Tablas de rendimiento / Performance tables

Tabla para: / Table for:

- Tobera regulable SR-3599
Adjustable nozzle SR-3599
- Difusores: / Pop-Up Spray:
 - serie Euro-Rain Caudal Normal / Normal Flow
 - serie Safe-Rain

Angulo de Riego	Presión Kg/cm2	Radio metros	Caudal LPM l/min
90°	1,5	4,00	4,00
	2,0	4,80	4,50
	2,5	4,90	5,00
	3,0	5,10	5,60
	3,5	5,50	6,00
180°	1,5	3,80	5,40
	2,0	4,20	6,00
	2,5	4,50	6,80
	3,0	5,00	7,40
	3,5	5,50	8,00
270°	1,5	3,20	6,00
	2,0	3,40	7,00
	2,5	3,50	8,00
	3,0	3,65	9,00
	3,5	3,90	10,00
360°	1,5	2,70	6,70
	2,0	2,90	7,80
	2,5	3,00	8,40
	3,0	3,40	9,30
	3,5	3,70	10,10

Tobera regulable SR-3599 Adjustable nozzle SR-3599

conexión H - Plastico
connection F - Plastic



Toberas / Nozzles serie 3300



conexión M - Latón / connection M - Brass

Ref.	Sector	Presión Pressure	Caudal / Flow L / min.	Radio / Range m.
3300	360°	1,5	12,84	3,60
		2,0	14,72	4,10
		2,5	16,40	4,30
3320	270°	1,5	6,80	4,40
		2,0	7,72	4,80
		2,5	9,00	4,80
3340	180°	1,5	3,20	4,00
		2,0	3,52	4,40
		2,5	4,18	4,80
3360	90°	1,5	3,20	4,00
		2,0	4,52	4,40
		2,5	4,18	4,80